

Serial No. 09/863,078
May 5, 2003
Page 2

BEST AVAILABLE COPY

BEST AVAILABLE COPY

IN THE CLAIMS:

1. (currently amended) A transformer comprising:

a bobbin having first and second tube-shaped members which are coaxial and integral with one another, said first tube-shaped member being located radially within said second tube-shaped member so as to form a gap located therebetween, and said first and second tube-shaped members being integral with and attached to a common base member;

a first winding comprising an air-core coil located in said gap between said first and second tube-shaped members of said bobbin; and

a second winding affixed to said second tube-shaped member of said bobbin.

a
2. (currently amended) A transformer according to Claim 1, wherein said air-core coil is not affixed to either said first or second tube-shaped members.

3. (original) A transformer according to Claim 1, wherein said first winding has a smaller number of turns than said second winding and serves as an input winding which allows a first current associated with a first voltage to flow therethrough, said second winding serving as an output winding which allows a second current associated with a second voltage, higher than said first voltage, to flow therethrough.

4. (original) A transformer according to one of Claim 3, further comprising a third winding wound on said second tube-shaped.

5. (original) A transformer according to Claim 4, wherein said third winding serves as a feedback winding which allows a current which is smaller than said second current to flow therethrough.

6. (original) A transformer according to one of Claim 1, further comprising a third winding, separate from said second winding, located on said second tube-shaped member.

Serial No. 09/863,078

May 5, 2003

Page 3

BEST AVAILABLE COPY

7. (original) A transformer according to Claim 6, wherein said third winding serves as a feedback winding which allows a current which is smaller than said second current to flow therethrough.

8. (original) A transformer according to claim 1, wherein said first and second tube-shaped members are coupled together by a radially extending base member.

a
9. (original) A transformer according to claim 8, further including terminals extending from said radially extending base member.

10. (original) A transformer according to claim 9, wherein at least two of said terminals are coupled to said secondary winding.

11. (currently amended) A transformer comprising:
a bobbin having first and second axially extending members which are coaxial and integral with one another, said first member being located radially within said second member so as to form a gap therebetween, and said first and second tube-shaped members being integral with and attached to a common base member;

a first winding comprising an air-core coil located in said gap; and
a second winding affixed to said second member.

12. (currently amended) A transformer according to Claim 11, wherein said air-core coil is not affixed to either said first or said second axially extending members.

13. (original) A transformer according to Claim 11, wherein said first winding has a smaller number of turns than said second winding and serves as an input winding which allows a first current associated with a first voltage to flow therethrough, said second winding serving as an output winding which allows a second current associated with a second voltage, higher than said first voltage, to flow therethrough.

Serial No. 09/863,078

May 5, 2003

Page 4

BEST AVAILABLE COPY

14. (original) A transformer according to one of Claim 13, further comprising a third winding wound on said second axially extending member.

15. (original) A transformer according to Claim 14, wherein said third winding serves as a feedback winding which allows a current which is smaller than said second current to flow therethrough.

a1
16. (original) A transformer according to one of Claim 1, further comprising a third winding, separate from said second winding, located on said second axially extending member.

17. (original) A transformer according to Claim 16, wherein said third winding serves as a feedback winding which allows a current which is smaller than said second current to flow therethrough.

18. (original) A transformer according to claim 1, wherein said first and second axially extending members are coupled together by a radially extending base member.

19. (original) A transformer according to claim 18, further including terminals extending from said radially extending base member.

20. (original) A transformer according to claim 19, wherein at least two of said terminals are coupled to said secondary winding.